



SW series

Swivel Joint Adjustable

DESIGN FEATURES

- Adjustable swivel joints facilitates alignment of spray nozzles
- Leak-proof design
- Standard materials are brass and stainless steel

- **Adjustment angles :** 40° to 70°
- Greater control of spray direction for precise coverage



FLOW SPECIFICATIONS		SIZE : BSP or NPT				
Model	A Inlet Pipe Conn.	B Outlet Pipe Conn.	C Overall Length (mm)	D Hex Size (mm)	E Hex Size (mm)	F Angle of Adjustment
1/8 X 1/8 SW	1/8M	1/8F	34.9	28.7	35.1	55°
1/4 X 1/4 SW	1/4M	1/4F	49.0	38.1	35.1	70°
3/8 X 1/4 SW	3/8M	1/4F	47.6	38.1	35.1	70°
3/8 X 3/8 SW	3/8M	3/8F	47.6	38.1	35.1	55°
1/2 X 3/8 SW	1/2M	3/8F	49.2	38.1	35.1	55°
1/2 X 1/2 SW	1/2M	1/2F	60.3	50.8	47.8	60°
1/2 X 3/4 SW	1/2M	3/4F	57.9	50.8	47.8	40°
3/4 X 1/2 SW	3/4M	1/2F	58.7	50.8	47.8	40°
3/4 X 3/4 SW	3/4M	3/4F	58.7	50.8	47.8	40°
1 X 1 SW	1M	1F	77.8	57.2	47.8	40°
1 1/4 X 1 1/4 SW	1 1/4M	1 1/4F	99.2	71.9	47.8	30°
1 1/2 X 1 1/2 SW	1 1/2M	1 1/2F	99.2	85.7	47.8	30°
2 X 2 SW	2M	2F	106	102	47.8	40°

